

# Modular Type Filter Regulators Series AW

| <b>Filter Regulator<br/>Series AW</b><br><br><br><br>Pages 516 through to 527                          | Model    | Port size     | Options                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------|---------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                                         | AW10     | M5 x 0.8      |                                                                                                                     |
|                                                                                                                                                                                         | AW20     | 1/8, 1/4      |                                                                                                                     |
|                                                                                                                                                                                         | AW30     | 1/4, 3/8      |                                                                                                                     |
|                                                                                                                                                                                         | AW40     | 1/4, 3/8, 1/2 |                                                                                                                     |
|                                                                                                                                                                                         | AW40-06  | 3/4           |                                                                                                                     |
|                                                                                                                                                                                         | AW60     | 3/4, 1        |                                                                                                                     |
| <b>Filter Regulator with Backflow Function<br/>Series AW□K</b><br><br><br><br>Pages 516 through to 527 | AW20K    | 1/8, 1/4      | Bracket<br><br>Float type auto drain<br><br>Square embedded type pressure gauge (except the AW10)                   |
|                                                                                                                                                                                         | AW30K    | 1/4, 3/8      |                                                                                                                     |
|                                                                                                                                                                                         | AW40K    | 1/4, 3/8, 1/2 |                                                                                                                     |
|                                                                                                                                                                                         | AW40K-06 | 3/4           |                                                                                                                     |
|                                                                                                                                                                                         | AW60K    | 3/4, 1        |                                                                                                                     |
| <b>Mist Separator Regulator<br/>Series AWM</b><br><br><br><br>Pages 528 through to 537                | AWM20    | 1/8, 1/4      | Round type pressure gauge<br><br>Digital pressure switch (except the AW10)<br><br>Panel mount (except the AW60 (K)) |
|                                                                                                                                                                                         | AWM30    | 1/4, 3/8      |                                                                                                                     |
|                                                                                                                                                                                         | AWM40    | 1/4, 3/8, 1/2 |                                                                                                                     |
| <b>Micro Mist Separator Regulator<br/>Series AWD</b><br><br><br><br>Pages 528 through to 537         | AWD20    | 1/8, 1/4      |                                                                                                                     |
|                                                                                                                                                                                         | AWD30    | 1/4, 3/8      |                                                                                                                     |
|                                                                                                                                                                                         | AWD40    | 1/4, 3/8, 1/2 |                                                                                                                     |



|       |
|-------|
| AC-A  |
| AF-A  |
| AF□-A |
| AR-A  |
| AL-A  |
| AW-A  |
| AC    |
| AF    |
| AF□   |
| AR    |
| AL    |
| AW□   |
| A□G   |
| E□    |
| AV    |
| AF    |

## Filter Regulator

# AW10 to AW60

## Filter Regulator with Backflow Function


# AW20K to AW60K



- Integrated filter and regulator units save space and require less piping.
- With the backflow function it incorporates a mechanism to exhaust the air pressure in the outlet side reliably and quickly.

Example)

When the air supply is cut off and releasing the inlet pressure to the atmosphere, the residual pressure release of the outlet side can be ensured for a safety purpose.



## How to Order

AW **30** **K** - **03** **BE** - **1** - **1**

① ② ③ ④ ⑤ ⑥

**Made to Order**

Refer to pages 524 through to 527 for details.

- Option/Semi-standard: Select one each for a to i.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.  
Example) AW30K-03BE-1N

|                 |                               | Symbol                     | Description                                                | ① Body size |    |    |    |    |
|-----------------|-------------------------------|----------------------------|------------------------------------------------------------|-------------|----|----|----|----|
|                 |                               |                            |                                                            | 10          | 20 | 30 | 40 | 60 |
| ②               | With backflow function        | Nil                        | Without backflow function                                  | ●           | ●  | ●  | ●  | ●  |
|                 |                               | K <small>Note 1)</small>   | With backflow function                                     | —           | ●  | ●  | ●  | ●  |
| ③               | Thread type                   | +                          | Metric thread (M5)                                         | ●           | —  | —  | —  | —  |
|                 |                               | Nil                        | Rc                                                         | —           | ●  | ●  | ●  | ●  |
|                 |                               | N <small>Note 2)</small>   | NPT                                                        | —           | —  | ●  | ●  | —  |
|                 |                               | F <small>Note 3)</small>   | G                                                          | —           | ●  | ●  | ●  | ●  |
| ④               | Port size                     | +                          | M5                                                         | ●           | —  | —  | —  | —  |
|                 |                               | 01                         | 1/8                                                        | —           | ●  | —  | —  | —  |
|                 |                               | 02                         | 1/4                                                        | —           | ●  | ●  | ●  | —  |
|                 |                               | 03                         | 3/8                                                        | —           | —  | ●  | ●  | —  |
|                 |                               | 04                         | 1/2                                                        | —           | —  | —  | ●  | —  |
|                 |                               | 06                         | 3/4                                                        | —           | —  | —  | ●  | ●  |
|                 |                               | 10                         | 1                                                          | —           | —  | —  | —  | ●  |
| ⑤ Option        | a Mounting                    | Nil                        | Without mounting option                                    | ●           | ●  | ●  | ●  | ●  |
|                 |                               | B <small>Note 5)</small>   | With bracket                                               | ●           | ●  | ●  | ●  | ●  |
|                 |                               | H                          | With set nut (for panel fitting)                           | ●           | ●  | ●  | ●  | —  |
|                 | b Float type auto drain       | +                          | Without auto drain                                         | ●           | ●  | ●  | ●  | ●  |
|                 |                               | C                          | Float type auto drain (N.C.)                               | ●           | ●  | ●  | ●  | ●  |
|                 |                               | D                          | Float type auto drain (N.O.)                               | —           | —  | ●  | ●  | ●  |
|                 | c Pressure gauge              | Nil                        | Without pressure gauge                                     | ●           | ●  | ●  | ●  | ●  |
|                 |                               | E                          | Square embedded type pressure gauge (with limit indicator) | —           | —  | —  | —  | —  |
|                 |                               | G                          | Round type pressure gauge (without limit indicator)        | ●           | —  | —  | —  | —  |
|                 |                               | G                          | Round type pressure gauge (with limit indicator)           | —           | ●  | ●  | ●  | ●  |
|                 |                               | M                          | Round type pressure gauge (with color zone)                | —           | —  | ●  | ●  | ●  |
|                 |                               | E1 <small>Note 6)</small>  | Output: NPN output / Electrical entry: Wiring bottom entry | —           | ●  | ●  | ●  | ●  |
|                 |                               | E2 <small>Note 6)</small>  | Output: NPN output / Electrical entry: Wiring top entry    | —           | ●  | ●  | ●  | ●  |
|                 |                               | E3 <small>Note 6)</small>  | Output: PNP output / Electrical entry: Wiring bottom entry | —           | ●  | ●  | ●  | ●  |
|                 |                               | E4 <small>Note 6)</small>  | Output: PNP output / Electrical entry: Wiring top entry    | —           | ●  | ●  | ●  | ●  |
| ⑥ Semi-standard | d Set pressure                | Nil <small>Note 7)</small> | 0.05 to 0.85 MPa setting                                   | ●           | ●  | ●  | ●  | ●  |
|                 |                               | 1 <small>Note 8)</small>   | 0.02 to 0.2 MPa setting                                    | ●           | ●  | ●  | ●  | ●  |
|                 | e Bowl <small>Note 9)</small> | +                          | Polycarbonate bowl                                         | ●           | ●  | ●  | ●  | ●  |
|                 |                               | 2                          | Metal bowl                                                 | ●           | ●  | ●  | ●  | ●  |
|                 |                               | 6                          | Nylon bowl                                                 | —           | ●  | ●  | ●  | ●  |
|                 |                               | 8                          | Metal bowl with level gauge                                | —           | —  | —  | ●  | ●  |
|                 |                               | C                          | With bowl guard                                            | —           | ●  | —  | —  | —  |
|                 |                               | 6C                         | Nylon bowl with bowl guard                                 | —           | —  | —  | —  | —  |

# Filter Regulator *Series AW10 to AW60*

## Filter Regulator with Backflow Function *Series AW20K to AW60K*



AW20, AW20K AW40, AW40K

|   |                   | Symbol                 | Description                                                                       | ①                     |                       |                       |                       |                       |
|---|-------------------|------------------------|-----------------------------------------------------------------------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
|   |                   |                        |                                                                                   | Body size             |                       |                       |                       |                       |
|   |                   |                        |                                                                                   | 10                    | 20                    | 30                    | 40                    | 60                    |
| f | Drain port        | Nil                    | With drain cock                                                                   | ●                     | ●                     | ●                     | ●                     | ●                     |
|   |                   | J <sup>Note 11)</sup>  | Drain guide 1/8                                                                   | —                     | ●                     | —                     | —                     | —                     |
|   |                   |                        | Drain guide 1/4                                                                   | —                     | —                     | ●                     | ●                     | ●                     |
|   |                   | W <sup>Note 12)</sup>  | Drain cock with barb fitting: For ø6 x ø4 nylon tube                              | —                     | —                     | ●                     | ●                     | ●                     |
|   |                   |                        |                                                                                   | +                     |                       |                       |                       |                       |
| g | Exhaust mechanism | Nil                    | Relieving type                                                                    | ●                     | ●                     | ●                     | ●                     | ●                     |
|   |                   | N                      | Non-relieving type                                                                | ●                     | ●                     | ●                     | ●                     | ●                     |
|   |                   |                        |                                                                                   | +                     |                       |                       |                       |                       |
| h | Flow direction    | Nil                    | Flow direction: Left to right                                                     | ●                     | ●                     | ●                     | ●                     | ●                     |
|   |                   | R                      | Flow direction: Right to left                                                     | ●                     | ●                     | ●                     | ●                     | ●                     |
|   |                   |                        |                                                                                   | +                     |                       |                       |                       |                       |
| i | Pressure unit     | Nil                    | Name plate, caution plate for bowl, and pressure gauge in imperial units: MPa     | ○                     | ●                     | ●                     | ●                     | ●                     |
|   |                   | Z <sup>Note 13)</sup>  | Name plate, caution plate for bowl, and pressure gauge in imperial units: psi, “F | ○ <sup>Note 15)</sup> | ○ <sup>Note 15)</sup> | ○ <sup>Note 15)</sup> | ○ <sup>Note 15)</sup> | ○ <sup>Note 15)</sup> |
|   |                   | ZA <sup>Note 14)</sup> | Digital pressure switch: With unit conversion function                            | —                     | △ <sup>Note 16)</sup> | △ <sup>Note 16)</sup> | △ <sup>Note 16)</sup> | △ <sup>Note 16)</sup> |

Note 1) The AW10 type comes with a backflow function as a standard feature. (K is not available.) When using the AW10 type as w/ backflow function, backflow may not occur with the set pressure 0.15 MPa or less. For AW20K to AW60K, Please set the inlet pressure to at least 0.05 MPa higher than the set pressure.

Note 2) Drain guide is NPT 1/8 (applicable to the AW20(K)) and NPT 1/4 (applicable to the AW30(K) to AW60(K)). The auto drain port comes with ø3/8" one-touch fitting (applicable to the AW30(K) to AW60(K)).

Note 3) Drain guide is G 1/8 (applicable to the AW20(K)) and G 1/4 (applicable to the AW30(K) to AW60(K)).

Note 4) Option B, G, H, M are not assembled and supplied loose at the time of shipment.

Note 5) Assembly of a bracket and set nuts (AW10,

AW20(K) to AW40(K)) including 2 mounting screws for the AW60(K)

Note 6) When choosing with H (panel mount), the installation space for lead wires will not be secured. In this case, select "wiring top entry" for the electrical entry.

Note 7) Only the AW10 has a pressure setting of 0.05 to 0.7 MPa.

Note 8) The only difference from the standard specifications is the adjusting spring for the regulator. It does not restrict the setting of 0.2 MPa or more. When the pressure gauge is attached, a 0.2 MPa pressure gauge will be fitted.

Note 9) Refer to Chemical Data on page 365 when selecting a case material.

Note 10) Float type auto drain: The combination of C and D is not possible.

Note 11) Without a valve function

Note 12) Metal bowl: The combination of 2 and 8 is not possible.

Note 13) For thread type: M5 and NPT. This product is for overseas use only according to the new Measurement Law. (The SI unit type is provided for use in Japan.) The digital pressure switch will be equipped with the unit conversion function, setting to psi initially.

The combination of the round type pressure gauge with color zone "M" and a psi display "Z" is not orderable as a standard product. However, this combination is available as a special.

Note 14) For options: E1, E2, E3, E4. This product is for overseas use only according to the new Measurement Law. (The SI unit is provided for use in Japan.)

Note 15) ○: For thread type: M5 and NPT only

Note 16) △: Select with options: E1, E2, E3, E4.

### Standard Specifications

| Model                                            | AW10                                                             | AW20(K)          | AW30(K)  | AW40(K)       | AW40(K)-06 | AW60(K) |
|--------------------------------------------------|------------------------------------------------------------------|------------------|----------|---------------|------------|---------|
| Port size                                        | M5 x 0.8                                                         | 1/8, 1/4         | 1/4, 3/8 | 1/4, 3/8, 1/2 | 3/4        | 3/4, 1  |
| Pressure gauge port size <sup>Note 1)</sup>      | 1/16 <sup>Note 2)</sup>                                          | 1/8              |          | 1/4           |            |         |
| Fluid                                            | Air                                                              |                  |          |               |            |         |
| Ambient and fluid temperature <sup>Note 3)</sup> | -5 to 60°C (with no freezing)                                    |                  |          |               |            |         |
| Proof pressure                                   | 1.5 MPa                                                          |                  |          |               |            |         |
| Maximum operating pressure                       | 1.0 MPa                                                          |                  |          |               |            |         |
| Set pressure range                               | 0.05 to 0.7 MPa                                                  | 0.05 to 0.85 MPa |          |               |            |         |
| Relief pressure <sup>Note 4)</sup>               | Set pressure + 0.05 MPa [at relief flow rate of 0.1 L/min (ANR)] |                  |          |               |            |         |
| Nominal filtration rating                        | 5 μm                                                             |                  |          |               |            |         |
| Drain capacity (cm³)                             | 2.5                                                              | 8                | 25       | 45            | 45         | 45      |
| Bowl material                                    | Polycarbonate                                                    |                  |          |               |            |         |
| Bowl guard                                       | —                                                                | Semi-standard    | Standard |               |            |         |
| Construction                                     | Relieving type                                                   |                  |          |               |            |         |
| Weight (kg)                                      | 0.09                                                             | 0.20             | 0.40     | 0.72          | 0.75       | 2.00    |

Note 1) Pressure gauge connection threads are not available for F.R.L. unit with a square embedded type pressure gauge (AW20(K) to AW60(K)).

Note 2) Use a bushing (part no.:131368) when connecting the R1/8 pressure gauge to the Rc 1/16.

Note 3) -5 to 50°C for the products with the digital pressure switch

Note 4) Not applicable to the AW10.

# Series AW10 to AW60

## Series AW20K to AW60K

### Options/Part No.

| Optional specifications                                             |                                                        |                         | Model                            |                                                   |             |              |            |                                    |  |
|---------------------------------------------------------------------|--------------------------------------------------------|-------------------------|----------------------------------|---------------------------------------------------|-------------|--------------|------------|------------------------------------|--|
|                                                                     |                                                        |                         | AW10                             | AW20(K)                                           | AW30(K)     | AW40(K)      | AW40(K)-06 | AW60(K)                            |  |
| Bracket assembly <small>Note 1)</small>                             |                                                        |                         | AR10P-270AS                      | AW20P-270AS                                       | AR30P-270AS | AR40P-270AS  |            | AW60P-270AS <small>Note 6)</small> |  |
| Set nut                                                             |                                                        |                         | AR10P-260S                       | AR20P-260S                                        | AR30P-260S  | AR40P-260S   |            | — <small>Note 7)</small>           |  |
| Pressure gauge                                                      | Round type <small>Note 2)</small>                      | Standard                | G27-10-R1                        | G36-10-□01                                        |             | G46-10-□02   |            |                                    |  |
|                                                                     |                                                        | 0.02 to 0.2 MPa setting | G27-10-R1 <small>Note 3)</small> | G36-2-□01                                         |             | G46-2-□02    |            |                                    |  |
|                                                                     | Round type <small>Note 2)</small><br>(with color zone) | Standard                | —                                | G36-10-□01-L                                      |             | G46-10-□02-L |            |                                    |  |
|                                                                     |                                                        | 0.02 to 0.2 MPa setting | —                                | G36-2-□01-L                                       |             | G46-2-□02-L  |            |                                    |  |
|                                                                     | Square embedded type <small>Note 4)</small>            | Standard                | —                                | GC3-10AS [GC3P-010AS (Pressure gauge cover only)] |             |              |            |                                    |  |
|                                                                     |                                                        | 0.02 to 0.2 MPa setting | —                                | GC3-2AS [GC3P-010AS (Pressure gauge cover only)]  |             |              |            |                                    |  |
| Digital pressure switch <small>Note 5)</small>                      | NPN output / Wiring bottom entry                       |                         | —                                | ISE35-N-25-MLA [ISE35-N-25-M (Switch body only)]  |             |              |            |                                    |  |
|                                                                     | NPN output / Wiring top entry                          |                         |                                  | ISE35-R-25-MLA [ISE35-R-25-M (Switch body only)]  |             |              |            |                                    |  |
|                                                                     | PNP output / Wiring bottom entry                       |                         |                                  | ISE35-N-65-MLA [ISE35-N-65-M (Switch body only)]  |             |              |            |                                    |  |
|                                                                     | PNP output / Wiring top entry                          |                         |                                  | ISE35-R-65-MLA [ISE35-R-65-M (Switch body only)]  |             |              |            |                                    |  |
|                                                                     |                                                        |                         |                                  |                                                   |             |              |            |                                    |  |
| <small>Note 8)</small> <small>Note 9)</small> Float type auto drain |                                                        |                         | N.C.                             | AD17                                              | AD27        | AD37         | AD47       |                                    |  |
|                                                                     |                                                        |                         | N.O.                             | —                                                 | —           | AD38         | AD48       |                                    |  |

### Semi-standard/Bowl Assembly Part No.

| Semi-standard specifications   |                                             |      |                                   |                         | Model                 |        |          |         |         |            |         |
|--------------------------------|---------------------------------------------|------|-----------------------------------|-------------------------|-----------------------|--------|----------|---------|---------|------------|---------|
| Bowl material                  | Note 8) Note 9)<br>Float type<br>auto drain |      | Note 9)<br>With<br>drain<br>guide | With<br>barb<br>fitting | With<br>bowl<br>guard | AW10   | AW20(K)  | AW30(K) | AW40(K) | AW40(K)-06 | AW60(K) |
|                                | N.C.                                        | N.O. |                                   |                         |                       |        |          |         |         |            |         |
| Polycarbonate                  | —                                           | —    | —                                 | —                       | ●                     | —      | C2SF-C   | —       | —       | —          | —       |
|                                | ●                                           | —    | —                                 | —                       | ●                     | —      | AD27-C   | —       | —       | —          | —       |
|                                | —                                           | —    | ●                                 | —                       | —                     | —      | C2SF-J   | C3SF-J  | —       | C4SF-J     | —       |
|                                | —                                           | —    | —                                 | ●                       | —                     | —      | —        | C3SF-W  | —       | C4SF-W     | —       |
|                                | —                                           | —    | ●                                 | —                       | ●                     | —      | C2SF-CJ  | —       | —       | —          | —       |
| Nylon                          | —                                           | —    | —                                 | —                       | —                     | C1SF-6 | C2SF-6   | C3SF-6  | —       | C4SF-6     | —       |
|                                | —                                           | —    | —                                 | —                       | ●                     | —      | C2SF-6C  | —       | —       | —          | —       |
|                                | ●                                           | —    | —                                 | —                       | —                     | AD17-6 | AD27-6   | AD37-6  | —       | AD47-6     | —       |
|                                | —                                           | ●    | —                                 | —                       | —                     | —      | —        | AD38-6  | —       | AD48-6     | —       |
|                                | ●                                           | —    | —                                 | —                       | ●                     | —      | AD27-6C  | —       | —       | —          | —       |
|                                | —                                           | —    | ●                                 | —                       | —                     | —      | C2SF-6J  | C3SF-6J | —       | C4SF-6J    | —       |
|                                | —                                           | —    | —                                 | ●                       | —                     | —      | —        | C3SF-6W | —       | C4SF-6W    | —       |
|                                | —                                           | —    | ●                                 | —                       | ●                     | —      | C2SF-6CJ | —       | —       | —          | —       |
| Metal                          | —                                           | —    | —                                 | —                       | —                     | C1SF-2 | C2SF-2   | C3SF-2  | —       | C4SF-2     | —       |
|                                | ●                                           | —    | —                                 | —                       | —                     | AD17-2 | AD27-2   | AD37-2  | —       | AD47-2     | —       |
|                                | —                                           | ●    | —                                 | —                       | —                     | —      | —        | AD38-2  | —       | AD48-2     | —       |
|                                | —                                           | —    | ●                                 | —                       | —                     | —      | C2SF-2J  | C3SF-2J | —       | C4SF-2J    | —       |
| Metal bowl with<br>level gauge | —                                           | —    | —                                 | —                       | —                     | —      | —        | C3LF-8  | —       | C4LF-8     | —       |
|                                | ●                                           | —    | —                                 | —                       | —                     | —      | —        | AD37-8  | —       | AD47-8     | —       |
|                                | —                                           | ●    | —                                 | —                       | —                     | —      | —        | AD38-8  | —       | AD48-8     | —       |
|                                | —                                           | —    | ●                                 | —                       | —                     | —      | —        | C3LF-8J | —       | C4LF-8J    | —       |

Note 1) Assembly of a bracket and set nuts

Note 2) □ in part numbers for a round pressure gauge indicates a type of connection thread. No indication is necessary for R; however, indicate N for NPT. Please contact SMC regarding the connection thread NPT and pressure gauge supply for psi unit specifications.

Note 3) Standard pressure gauge

Note 4) Including one O-ring and 2 mounting screws. [ ] : Pressure gauge cover only

Note 5) Lead wire with connector (2 m), adapter, lock pin, O-ring (1 pc.), mounting screw (2 pcs.) are attached. [ ] : Switch body only. Also, regarding how to order the digital pressure switch, please refer to page 538. A pressure switch adapter assembly (AW60P-310AS) will be additionally required for the AW60(K) only. Use the attached mounting screw (M3 x 0.5 x 14) for mounting. The mounting screw (M3 x 0.5 x 7) attached to the digital pressure switch assembly will not be required.

Note 6) Assembly of a bracket and 2 mounting screws

Note 7) Please consult SMC regarding the set nuts for the AW60(K).

Note 8) Minimum operating pressure: N.O. type—0.1 MPa; N.C. type—0.1 MPa (AD27) and 0.15 MPa (AD37/47). Please contact SMC for psi and "F unit specifications.

Note 9) Please consult SMC for details on drain piping to fit NPT or G port sizes.

Note 9) Bowl O-ring is included for the AW20(K) to AW60(K).

• Bowl assembly for the AW30(K) to AW60(K) models comes with a bowl guard (steel band material). (except when the bowl material is metal)



# Series AW10 to AW60 Series AW20K to AW60K Specific Product Precautions

Be sure to read before handling. Refer to front matter 43 for Safety Instructions and pages 365 to 369 for F.R.L. Precautions.

## Selection

### Warning

1. Residual pressure disposal (outlet pressure removal) is not possible for the AW20 to AW60 even though the inlet pressure is exhausted. When the residual pressure disposal is performed, use the filter regulator with backflow function (AW20K to AW60K).

## Maintenance

### Warning

1. Replace the element every 2 years or when the pressure drop becomes 0.1 MPa, whichever comes first, to prevent damage to the element.

## Mounting and Adjustment

### Warning

1. Set the regulator while verifying the displayed values of the inlet and outlet pressure gauges. Turning the regulator knob excessively can cause damage to the internal parts.
2. The pressure gauge included with regulators for 0.02 to 0.2 MPa setting is for up to 0.2 MPa use only (except the AW10). Exceeding 0.2 MPa of pressure can damage the gauge.
3. Do not use tools on the pressure regulator knob as this may cause damage. It must be operated manually.

### Caution

1. Be sure to unlock the knob before adjusting the pressure and lock it after setting the pressure. Failure to follow this procedure can cause damage to the knob and the outlet pressure may fluctuate.
  - Pull the pressure regulator knob to unlock. (You can visually verify this with the "orange mark" that appears in the gap.)
  - Push the pressure regulator knob to lock. When the knob is not easily locked, turn it left and right a little and then push it (when the knob is locked, the "orange mark", i.e., the gap will disappear).



2. A knob cover is available to prevent careless operation of the knob. Refer to page 539 for details.

AC-A

AF-A

AF□-A

AR-A

AL-A

AW-A

AC

AF

AF□

AR

AL

AW□

A□G

E□

AV







AF

# Series AW10 to AW60

# Series AW20K to AW60K







## Flow Characteristics (Representative values)

Condition: Inlet pressure 0.7 MPa



## Pressure Characteristics (Representative values)


Conditions: Inlet pressure 0.7 MPa, Outlet pressure 0.2 MPa, Flow rate 20 L/min (ANR)



# Filter Regulator *Series AW10 to AW60*

## Filter Regulator with Backflow Function *Series AW20K to AW60K*

### Construction



|       |
|-------|
| AC-A  |
| AF-A  |
| AF□-A |
| AR-A  |
| AL-A  |
| AW-A  |
| AC    |
| AF    |
| AF□   |
| AR    |
| AL    |
| AW□   |
| A□G   |
| E□    |
| AV    |
| AF    |

### Component Parts

| No. | Description | Material          | Model              | Color           |
|-----|-------------|-------------------|--------------------|-----------------|
| 1   | Body        | Zinc die-cast     | AW10               | Platinum silver |
|     |             | Aluminum die-cast | AW20(K) to AW60(K) |                 |
| 2   | Bonnet      | Polycetal         | AW10 to AW40(K)    | Black           |
|     |             | Aluminum die-cast | AW60(K)            |                 |
| 3   | Housing     | Aluminum die-cast | AW60(K)            | Platinum silver |

### Replacement Parts

| No. | Description                             | Material         | Part no.                       |             |                         |                         |  |             |
|-----|-----------------------------------------|------------------|--------------------------------|-------------|-------------------------|-------------------------|--|-------------|
|     |                                         |                  | AW10                           | AW20(K)     | AW30(K)                 | AW40(K)                 |  | AW40(K)-06  |
| 4   | Valve assembly                          | Brass, HNBR      | AR10P-090S                     | AW20P-340AS | AW30P-340AS             | AW40P-340AS             |  | AW60P-090AS |
| 5   | Filter element                          | Non-woven fabric | AF10P-060S                     | AF20P-060S  | AF30P-060S              | AF40P-060S              |  | AW60P-060S  |
| 6   | Diaphragm assembly                      | Weatherable NBR  | AR10P-150AS <sup>Note 1)</sup> | AR20P-150AS | AR30P-150AS             | AR40P-150AS             |  | AR50P-150AS |
| 7   | Bowl O-ring                             | NBR              | C1SFP-260S                     | C2SFP-260S  | C3SFP-260S              | C4SFP-260S              |  |             |
| 8   | Bowl assembly <sup>Note 2)</sup>        | Polycarbonate    | C1SF                           | C2SF        | C3SF <sup>Note 3)</sup> | C4SF <sup>Note 3)</sup> |  |             |
| 9   | Check valve assembly <sup>Note 4)</sup> | —                | —                              | —           | AR20KP-020AS            |                         |  |             |

Note 1) The AW10 is a piston type. Assembly of a piston and a seal (KSPY-13).

Note 2) Bowl O-ring is included for the AW20(K) to AW60(K). Please contact SMC regarding the bowl assembly supply for psi and "F" unit specifications.

Note 3) Bowl assembly for the AW30(K) to AW60(K) models comes with a bowl guard (steel band material).

Note 4) Check valve assembly is applicable for a filter regulator with backflow function (AW20K to AW60K) only.



Assembly of a check valve cover, check valve body assembly and 2 screws

# Series AW10 to AW60

## Series AW20K to AW60K

### Working Principle (Filter Regulator with Backflow Function)

#### AW10



When the inlet pressure is higher than the regulating pressure, the check valve operates as a normal regulator (Figure 1). When the inlet pressure is shut off and exhausted, any inlet pressure applied to the valve ① will be lost. The force for seating the valve ① is the valve spring force ② only. When the valve ① is opened using the outlet force, the outlet pressure will be exhausted at the inlet side. (Figure 2)

When the set pressure is 0.15 MPa or less, valve ① may not open due to the valve spring ② force.

#### AW20K to AW60K




Figure 1 Normal




Figure 2 Backflow

When the inlet pressure is higher than the regulating pressure, the check valve ② closes and operates as a normal regulator (Figure 1). When the inlet pressure is shut off and released, the check valve ② opens and the pressure in the diaphragm chamber ① is released into the inlet side (Figure 2).


This lowers the pressure in the diaphragm chamber ① and the force generated by the pressure regulator spring ③ lifts the diaphragm. Valve ④ opens through the stem, and the outlet pressure is released to the inlet side (Figure 2).

# Filter Regulator *Series AW10 to AW60*

## Filter Regulator with Backflow Function *Series AW20K to AW60K*

### Dimensions

#### AW10, AW20(K)



Panel fitting dimension






Plate thickness  
AW10, AW20(K): Max. 3.5

#### AW60(K)



#### AW30(K) to AW40(K)-06



Panel fitting dimension




Plate thickness  
AW30(K): Max. 3.5  
AW40(K): Max. 5

| Applicable model | AW20(K) to AW60(K)                  |                         | AW10, AW20(K) to AW60(K)  | AW20(K) to AW60(K)                          |
|------------------|-------------------------------------|-------------------------|---------------------------|---------------------------------------------|
| Option           | Square embedded type pressure gauge | Digital pressure switch | Round type pressure gauge | Round type pressure gauge (with color zone) |
| Dimensions       |                                     |                         |                           |                                             |

| Applicable model                      | AW10, AW20(K)                                                                                   |                                                                                     | AW20(K)                                                                                                             | AW30(K) to AW60(K)                                                                                                                        |                                                                                     |                                                                                     |                                                                                                                     |                                                                                                                                   |
|---------------------------------------|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Optional/Semi-standard specifications | With auto drain (N.C.)                                                                          | Metal bowl                                                                          | With drain guide                                                                                                    | With auto drain (N.O./N.C.)                                                                                                               | Metal bowl                                                                          | Metal bowl with level gauge                                                         | With drain guide                                                                                                    | Drain cock with barb fitting                                                                                                      |
| Dimensions                            | <br>M5 x 0.8 |  | <br>1/8<br>Width across flats 14 | <br>N.O.: Black<br>N.C.: Gray<br>ø10 one-touch fitting |  |  | <br>1/4<br>Width across flats 17 | <br>Barb fitting<br>Applicable tubing: T0604 |

| Model      | Standard specifications |      |    |          |     |      |      |           |    |      |     | Optional specifications |      |       |      |       |      |       |    |
|------------|-------------------------|------|----|----------|-----|------|------|-----------|----|------|-----|-------------------------|------|-------|------|-------|------|-------|----|
|            | P1                      | P2   | A  | B (Note) | C   | D    | E    | F         | G  | J    | K   | H                       | J    | H     | J    | H     | J    | H     | J  |
| AW10       | M5 x 0.8                | 1/16 | 25 | 108      | 48  | 12.5 | —    | M18 x 1   | 25 | 12.5 | 0   | —                       | —    | —     | —    | —     | —    | —     | —  |
| AW20(K)    | 1/8, 1/4                | 1/8  | 40 | 160      | 73  | 26   | —    | M28 x 1   | 40 | 26   | 5   | □28                     | 27   | □27.8 | 37.5 | □37.5 | 62.5 | □37.5 | 63 |
| AW30(K)    | 1/4, 3/8                | 1/8  | 53 | 201      | 86  | 29.5 | 30   | M38 x 1.5 | 55 | 29.5 | 3.5 | □28                     | 30.5 | □27.8 | 41   | □37.5 | 66   | □37.5 | 66 |
| AW40(K)    | 1/4, 3/8, 1/2           | 1/4  | 70 | 239      | 92  | 37.5 | 38   | M42 x 1.5 | 80 | 37.5 | 1.5 | □28                     | 38.5 | □27.8 | 49   | □42.5 | 76   | □42.5 | 76 |
| AW40(K)-06 | 3/4                     | 1/4  | 75 | 242      | 93  | 37.5 | 38   | M42 x 1.5 | 80 | 37.5 | 1.2 | □28                     | 38.5 | □27.8 | 49   | □42.5 | 76   | □42.5 | 76 |
| AW60(K)    | 3/4, 1                  | 1/4  | 95 | 409      | 175 | 43.5 | 47.5 | —         | 20 | 43.5 | 3.2 | □28                     | 44.5 | □27.8 | 61.5 | □42.5 | 82   | □42.5 | 84 |

| Model      | Optional specifications |    |    |     |      |             |     |      |      |    |   | Semi-standard specifications |                   |                  |            |                             |          |
|------------|-------------------------|----|----|-----|------|-------------|-----|------|------|----|---|------------------------------|-------------------|------------------|------------|-----------------------------|----------|
|            | Bracket mount           |    |    |     |      | Panel mount |     |      |      |    |   | With auto drain              | With barb fitting | With drain guide | Metal bowl | Metal bowl with level gauge |          |
|            | M                       | N  | Q  | R   | S    | T           | U   | V    | W    | Y  | Z | B (Note)                     | B (Note)          | B (Note)         | B (Note)   | B (Note)                    | B (Note) |
| AW10       | 25                      | 28 | 30 | 4.5 | 6.5  | 4.0         | 2   | 18   | 18.5 | —  | — | 125                          | —                 | —                | 107        | —                           | —        |
| AW20(K)    | 30                      | 34 | 44 | 5.4 | 15.4 | 55          | 2.3 | 30   | 28.5 | 14 | 6 | 177                          | —                 | 164              | 160        | —                           | —        |
| AW30(K)    | 41                      | 40 | 46 | 6.5 | 8    | 53          | 2.3 | 31   | 38.5 | 19 | 7 | 242                          | 209               | 208              | 214        | 234                         | —        |
| AW40(K)    | 50                      | 54 | 54 | 8.5 | 10.5 | 70          | 2.3 | 35.5 | 42.5 | 21 | 7 | 278                          | 247               | 246              | 252        | 272                         | —        |
| AW40(K)-06 | 50                      | 54 | 56 | 8.5 | 10.5 | 70          | 2.3 | 37   | 42.5 | 21 | 7 | 282                          | 251               | 249              | 255        | 275                         | —        |
| AW60(K)    | 70                      | 66 | 66 | 11  | 13   | 90          | 3.2 | —    | —    | —  | — | 448                          | 417               | 416              | 422        | 442                         | —        |

Note) The total length of B dimension is the length when the filter regulator knob is unlocked.



# Filter Regulator AW20 to AW60

## Made to Order Specifications:



Please contact SMC for detailed dimensions, specifications, and lead times.

### ① Special Temperature Environment

Special materials are used in the manufacturing of seals and resin parts to allow them to withstand various temperature conditions in cold or tropical (hot) climates.

#### Specifications

| Made-to-order part no.   | -X430                       | -X440                           |
|--------------------------|-----------------------------|---------------------------------|
| Environment              | Low temperature             | High temperature                |
| Ambient temperature (°C) | -30 to 60                   | -5 to 80                        |
| Fluid temperature (°C)   | -5 to 60 (with no freezing) |                                 |
| Material                 | Rubber parts                | Special NBR FKM                 |
|                          | Main parts                  | Metal (Aluminum die-cast), etc. |

#### Applicable Model

| Model     | AW30     | AW40          | AW40-06 | AW60   |
|-----------|----------|---------------|---------|--------|
| Port size | 1/4, 3/8 | 1/4, 3/8, 1/2 | 3/4     | 3/4, 1 |

AW **30** - **03** **BG** - **2** - **X430**

① ② ③ ④ ⑤ ⑥

For high/low temperature

|      |                  |
|------|------------------|
| X430 | Low temperature  |
| X440 | High temperature |



AW30-03G-2-X440

- Option/Semi-standard: Select one each for a to g.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.  
Example) AW30-03BG-2N-X430

|   | Symbol              | Description | ①          |            |            |
|---|---------------------|-------------|------------|------------|------------|
|   |                     |             | Body size  |            |            |
|   |                     |             | 30         | 40         | 60         |
| ② | Thread type         | NII         | ●          | ●          | ●          |
|   |                     | N           | ●          | ●          | ●          |
|   |                     | F           | ●          | ●          | ●          |
| ③ | Port size           | +           |            |            |            |
|   |                     | 02          | ●          | ●          | —          |
|   |                     | 03          | ●          | ●          | —          |
|   |                     | 04          | —          | ●          | —          |
|   |                     | 06          | —          | ●          | ●          |
|   |                     | 1           | —          | —          | ●          |
| ④ | a Mounting          | +           |            |            |            |
|   |                     | NII         | ●          | ●          | ●          |
|   |                     | B (Note 2)  | ●          | ●          | ●          |
|   | b Pressure gauge    | H           | ●          | ●          | —          |
|   |                     | +           |            |            |            |
|   |                     | NII         | ●          | ●          | ●          |
| ⑤ | c Set pressure      | G (Note 3)  | ●          | ●          | ●          |
|   |                     | +           |            |            |            |
|   |                     | NII         | ●          | ●          | ●          |
|   | d Drain port        | 1 (Note 5)  | ●          | ●          | ●          |
|   |                     | +           |            |            |            |
|   |                     | NII         | ●          | ●          | ●          |
| ⑥ | e Exhaust mechanism | J (Note 6)  | ●          | ●          | ●          |
|   |                     | +           |            |            |            |
|   |                     | NII         | ●          | ●          | ●          |
|   | f Flow direction    | N           | ●          | ●          | ●          |
|   |                     | +           |            |            |            |
|   |                     | R           | ●          | ●          | ●          |
| ⑦ | g Pressure unit     | +           |            |            |            |
|   |                     | NII         | ●          | ●          | ●          |
|   |                     | Z (Note 7)  | ○ (Note 8) | ○ (Note 8) | ○ (Note 8) |

Note 1) Option B, G, H are not assembled and supplied loose at the time of shipment.

Note 2) Assembly of a bracket and set nuts (AW30 to AW40)

Note 3) Including 2 mounting screws for the AW60

Note 4) Mounting thread for pressure gauge: 1/8 for the AW30, 1/4 for the AW40 and AW60. Pressure gauge type: G43

Note 5) Only metal bowl 2 is available.

Note 6) The only difference from the standard specifications is the adjusting spring for the regulator. It does not restrict the setting of 0.2 MPa or more. When the pressure gauge is attached, a 0.2 MPa pressure gauge will be fitted.

Note 7) Without a valve function

Note 8) For thread type: NPT. This product is for overseas use only according to the new Measurement Law. (The SI unit type is provided for use in Japan.)

Note 9) ○: For thread type: NPT only

## ② High Pressure

Strong materials are used in the manufacturing of air filters intended for high pressure operation. Also, construction modification allows a wider regulating pressure range.

### Specifications

|                                    |                               |
|------------------------------------|-------------------------------|
| Made-to-order part no.             | -X425                         |
| Proof pressure (MPa)               | 3.0                           |
| Maximum operating pressure (MPa)   | 2.0                           |
| Set pressure range (MPa)           | 0.1 to 1.7                    |
| Ambient and fluid temperature (°C) | -5 to 60°C (with no freezing) |

### Applicable Model

| Model     | AW20     | AW30     | AW40          | AW40-06 | AW60   |
|-----------|----------|----------|---------------|---------|--------|
| Port size | 1/8, 1/4 | 1/4, 3/8 | 1/4, 3/8, 1/2 | 3/4     | 3/4, 1 |

AW **30** - **03** **BG** - **2** **1** - X425

1 2 3 4 5 6

For high pressure •



AW30-03-2-X425

- Option/Semi-standard: Select one each for a to f.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.  
Example) AW30-03BG-2N-X425

|                    |                     | Symbol    | Description                                                                       | ①<br>Body size |           |           |           |
|--------------------|---------------------|-----------|-----------------------------------------------------------------------------------|----------------|-----------|-----------|-----------|
|                    |                     |           |                                                                                   | 20             | 30        | 40        | 60        |
| ②                  | Thread type         | NII       | Rc                                                                                | ●              | ●         | ●         | ●         |
|                    |                     | N         | NPT                                                                               | ●              | ●         | ●         | ●         |
|                    |                     | F         | G                                                                                 | ●              | ●         | ●         | ●         |
| ③                  | Port size           | +         |                                                                                   |                |           |           |           |
|                    |                     | 01        | 1/8                                                                               | ●              | —         | —         | —         |
|                    |                     | 02        | 1/4                                                                               | —              | ●         | ●         | —         |
|                    |                     | 03        | 3/8                                                                               | —              | —         | ●         | —         |
|                    |                     | 04        | 1/2                                                                               | —              | —         | ●         | —         |
|                    |                     | 06        | 3/4                                                                               | —              | —         | ●         | ●         |
|                    |                     | 1         | 1                                                                                 | —              | —         | —         | ●         |
| ④<br>Option 1)     | a Mounting          | NII       | Without mounting option                                                           | ●              | ●         | ●         | ●         |
|                    |                     | B Note 2) | With bracket                                                                      | ●              | ●         | ●         | ●         |
|                    |                     | H         | With set nut (for panel fitting)                                                  | ●              | ●         | ●         | —         |
|                    | b Pressure gauge    | +         |                                                                                   |                |           |           |           |
|                    |                     | NII       | Without pressure gauge                                                            | ●              | ●         | ●         | ●         |
| ⑤                  | Bowl Note 4)        | G Note 3) | Round type pressure gauge (with limit indicator)                                  | ●              | ●         | ●         | ●         |
|                    |                     | +         |                                                                                   |                |           |           |           |
|                    |                     | 2         | Metal bowl                                                                        | ●              | ●         | ●         | ●         |
| ⑥<br>Semi-standard | c Exhaust mechanism | 8         | Metal bowl with level gauge                                                       | —              | ●         | ●         | ●         |
|                    |                     | +         |                                                                                   |                |           |           |           |
|                    | d Drain port        | NII       | Relieving type                                                                    | ●              | ●         | ●         | ●         |
|                    |                     | N         | Non-relieving type                                                                | ●              | ●         | ●         | ●         |
|                    |                     | +         |                                                                                   |                |           |           |           |
|                    | e Flow direction    | NII       | With drain cock                                                                   | ●              | ●         | ●         | ●         |
|                    |                     | J Note 5) | Drain guide 1/8                                                                   | ●              | —         | —         | —         |
|                    |                     |           | Drain guide 1/4                                                                   | —              | ●         | ●         | ●         |
|                    | f Pressure unit     | +         |                                                                                   |                |           |           |           |
|                    |                     | NII       | Flow direction: Left to right                                                     | ●              | ●         | ●         | ●         |
|                    |                     | R         | Flow direction: Right to left                                                     | ●              | ●         | ●         | ●         |
|                    |                     | +         |                                                                                   |                |           |           |           |
|                    |                     | NII       | Name plate, caution plate for bowl, and pressure gauge in imperial units: MPa     | ●              | ●         | ●         | ●         |
|                    |                     | Z Note 6) | Name plate, caution plate for bowl, and pressure gauge in imperial units: psi, °F | ○ Note 7)      | ○ Note 7) | ○ Note 7) | ○ Note 7) |
|                    |                     |           |                                                                                   |                |           |           |           |

Note 1) Option B, G, H are not assembled and supplied loose at the time of shipment.

Note 2) Assembly of a bracket and set nuts (AW20 to AW40)

Including 2 mounting screws for the AW60

Note 3) Mounting thread for pressure gauge: 1/8 for the AW20 and AW30, 1/4 for the AW40 and AW60. Pressure gauge type: G46-20-□

Note 4) Only metal bowl 2 and 8 are available.

Note 5) Without a valve function

Note 6) For thread type: NPT. This product is for overseas use only according to the new Measurement Law. (The SI unit type is provided for use in Japan.)

Note 7) ○: For thread type: NPT only

# Filter Regulator **AW10 to AW60** Filter Regulator with Backflow Function **AW20K to AW60K** Made to Order Specifications:



Please contact SMC for detailed dimensions, specifications, and lead times.

## ③ 0.4 MPa Setting

The maximum set pressure is 0.4 MPa. When a pressure gauge is included, the display will show a range from 0 to 0.4 MPa.

## Specifications

|                            |                 |
|----------------------------|-----------------|
| Proof pressure             | 1.5 MPa         |
| Maximum operating pressure | 1.0 MPa         |
| Set pressure range         | 0.05 to 0.4 MPa |

## Applicable Model

| Model     | AW10 | AW20(K)  | AW30(K)  | AW40(K)       | AW40(K)-06 | AW60(K) |
|-----------|------|----------|----------|---------------|------------|---------|
| Port size | M5   | 1/8, 1/4 | 1/4, 3/8 | 1/4, 3/8, 1/2 | 3/4        | 3/4, 1  |

## ④ Long Bowl

Drain capacity is greater than that of standard models.

## Applicable Model/Drain Capacity

| Model                             | AW10 | AW20(K)  | AW30(K)  | AW40(K)       | AW40(K)-06 | AW60(K) |
|-----------------------------------|------|----------|----------|---------------|------------|---------|
| Port size                         | M5   | 1/8, 1/4 | 1/4, 3/8 | 1/4, 3/8, 1/2 | 3/4        | 3/4, 1  |
| Drain capacity (cm <sup>3</sup> ) | 9    | 19       | 43       | 88            |            |         |

Note) Please consult SMC for dimensions.

## How to Order

|    |    |   |   |    |   |   |                                       |
|----|----|---|---|----|---|---|---------------------------------------|
| AW | 30 |   |   | 03 |   |   | X406                                  |
|    | 1  | 2 | 3 | 4  | 5 | 6 |                                       |
|    |    |   |   |    |   |   | X406 0.4 MPa setting<br>X64 Long bowl |

- Option/Semi-standard: Select one each for **a** to **h**.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.  
Example) AW30K-03BE-2N-X406

|          |                         | Symbol     | Description                                                | ① Body size |    |    |    |    | ① Body size |    |    |    |    |
|----------|-------------------------|------------|------------------------------------------------------------|-------------|----|----|----|----|-------------|----|----|----|----|
|          |                         |            |                                                            | 10          | 20 | 30 | 40 | 60 | 10          | 20 | 30 | 40 | 60 |
| ②        | With backflow function  | Nil        | Without backflow function                                  | ●           | ●  | ●  | ●  | ●  | ●           | ●  | ●  | ●  | ●  |
|          |                         | K Note 1)  | With backflow function                                     | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
| ③        | Thread type             | Nil        | Metric thread (M5)                                         | ●           | —  | —  | —  | —  | ●           | —  | —  | —  | —  |
|          |                         | N Note 2)  | Rc                                                         | —           | —  | ●  | ●  | ●  | —           | —  | ●  | ●  | ●  |
|          |                         | F Note 3)  | NPT                                                        | —           | —  | ●  | ●  | ●  | —           | —  | ●  | ●  | ●  |
|          |                         |            | G                                                          | —           | —  | ●  | ●  | ●  | —           | —  | ●  | ●  | ●  |
| ④        | Port size               | M5         | M5                                                         | ●           | —  | —  | —  | —  | ●           | —  | —  | —  | —  |
|          |                         | 01         | 1/8                                                        | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | 02         | 1/4                                                        | —           | —  | ●  | ●  | —  | —           | —  | ●  | ●  | —  |
|          |                         | 03         | 3/8                                                        | —           | —  | ●  | ●  | —  | —           | —  | ●  | ●  | —  |
|          |                         | 04         | 1/2                                                        | —           | —  | —  | —  | —  | —           | —  | —  | ●  | —  |
|          |                         | 06         | 3/4                                                        | —           | —  | —  | —  | —  | —           | —  | —  | —  | ●  |
|          |                         | 10         | 1                                                          | —           | —  | —  | —  | —  | —           | —  | —  | —  | ●  |
| ⑤ Option | a Mounting              | Nil        | Without mounting option                                    | ●           | ●  | ●  | ●  | ●  | ●           | ●  | ●  | ●  | ●  |
|          |                         | B Note 5)  | With bracket                                               | ●           | ●  | ●  | ●  | ●  | ●           | ●  | ●  | ●  | ●  |
|          |                         | H          | With set nut (for panel fitting)                           | ●           | ●  | ●  | ●  | —  | —           | —  | —  | —  | —  |
|          | b Float type auto drain | Nil        | Without auto drain                                         | ●           | ●  | ●  | ●  | ●  | —           | —  | —  | —  | —  |
|          |                         | C          | Float type auto drain (N.C.)                               | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | D          | Float type auto drain (N.O.)                               | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          | c Pressure gauge        | Nil        | Without pressure gauge                                     | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | E          | Square embedded type pressure gauge (with limit indicator) | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | G          | Round type pressure gauge (without limit indicator)        | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | M          | Round type pressure gauge (with limit indicator)           | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | M          | Round type pressure gauge (with color zone)                | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | E1 Note 6) | Output: NPN output / Electrical entry: Wiring bottom entry | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | E2 Note 6) | Output: NPN output / Electrical entry: Wiring top entry    | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          | Digital pressure switch | E3 Note 6) | Output: PNP output / Electrical entry: Wiring bottom entry | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |
|          |                         | E4 Note 6) | Output: PNP output / Electrical entry: Wiring top entry    | —           | —  | —  | —  | —  | —           | —  | —  | —  | —  |

Note 1) The AW10 type comes with a backflow function as a standard feature. (K is not available.) When using the AW10 type as w/ backflow function, backflow may not occur with the set pressure 0.15 MPa or less. Please set the inlet pressure to at least 0.05 MPa higher than the set pressure.

Note 2) Drain guide is NPT 1/8 (applicable to the AW20(K)) and NPT 1/4 (applicable to the AW30(K) to AW60(K)). The auto drain port comes with e3/8" One-touch fitting (applicable to the AW30(K) to AW60(K)).

Note 3) Drain guide is G 1/8 (applicable to the AW20(K)) and G 1/4 (applicable to the AW30(K) to AW60(K)).

Note 4) Option B, G, H, M are not assembled and supplied loose at the time of shipment.

Note 5) Assembly of a bracket and set nuts. (AW10, AW20(K) to AW40(K)). Including 2 mounting screws for the AW60(K)

Note 6) When choosing with H (panel mount), the installation space for lead wires will not be secured. In this case, select "wiring down entry" for the electrical entry.



## Lubricator

### How To Order

## Series AL20 to 40

**AL 20 — N 02 B — 2 Z - X480**

• Lubricator

• Body Size

| Symbol | Size |
|--------|------|
| 20     | 1/8  |
| 30     | 3/8  |
| 40     | 1/2  |

• NPT Threads

• Port Size

| Symbol | Port Size | Applicable Body Size |
|--------|-----------|----------------------|
| 02     | 1/4       | 20                   |
| 03     | 3/8       | 30                   |
| 04     | 1/2       | 40                   |

• Bowl

| Symbol | Description                 | Applicable Body Size |
|--------|-----------------------------|----------------------|
| 2      | Metal Bowl                  | 20                   |
| 8      | Metal Bowl with Sight Glass | 30, 40               |

• Accessories

| Symbol | Description      | Applicable Body Size |
|--------|------------------|----------------------|
| Nil    | None             | All                  |
| B*     | Mounting Bracket | All                  |

\*Note: Bracket is not assembled and is supplied loose at time of shipment.

• With External Epoxy Coating, Stainless Fasteners

• Name Plate, Caution Plate On Bowl in psi, °F

## Filter – Regulator

### How To Order

## Series AW20 to 40

**AW 30 — N 03 D 8 Z - X48**

• Filter - Regulator

• Body Size

| Symbol | Size |
|--------|------|
| 20     | 1/8  |
| 30     | 3/8  |
| 40     | 1/2  |

• NPT Threads

• Port Size

| Symbol | Port Size | Applicable Body Size |
|--------|-----------|----------------------|
| 02     | 1/4       | 20                   |
| 03     | 3/8       | 30                   |
| 04     | 1/2       | 40                   |

• Accessories

| Symbol | Description             | Applicable Body Size |
|--------|-------------------------|----------------------|
| Nil    | None                    | All                  |
| B*     | Mounting Bracket        | All                  |
| C      | Float Auto Drain (N.C.) | 30, 40               |
| D      | Float Auto Drain (N.O.) | 30, 40               |
| H*     | Panel Mount Nut         | All                  |

\*Note: Bracket and/or panel mount nut are not assembled and are supplied loose at time of shipment.

• With External Epoxy Coating Stainless Fasteners

• Name Plate in imperial Units (psi, °F)

• Bowl

| Symbol | Description                 | Applicable Body Size |
|--------|-----------------------------|----------------------|
| 2      | Metal Bowl                  | 20                   |
| 8      | Metal Bowl with Sight Glass | 30, 40               |

## U.S. & Canadian Sales Offices

| EAST       | WEST          | MIDWEST      | CANADA              |
|------------|---------------|--------------|---------------------|
| Atlanta    | Austin        | Chicago      | Montreal            |
| Boston     | Dallas        | Cincinnati   | Tel: (514) 733-9595 |
| Charlotte  | Los Angeles   | Cleveland    | Fax: (514) 733-1771 |
| Nashville  | Phoenix       | Detroit      | Toronto             |
| New Jersey | Portland      | Indianapolis | Tel: (905) 812-0400 |
| Richmond   | San Francisco | Milwaukee    | Fax: (905) 812-8686 |
| Rochester  |               | Minneapolis  | Vancouver           |
| Tampa      |               | St. Louis    | Tel: (604) 517-1646 |
|            |               |              | Fax: (604) 517-1647 |
|            |               |              | Windsor             |
|            |               |              | Tel: (519) 944-0555 |
|            |               |              | Fax: (519) 944-1870 |



SMC Corporation of America  
3011 N. Franklin Road  
Indianapolis, IN 46226

(800) 762-7621 (SMC.SMC1)  
www.smcusa.com

For International inquiries: www.smcworld.com

SMC Pneumatics (Canada) Ltd.  
6768 Financial Drive Mississauga  
Ontario, L5N 7J6 Canada

(905) 812-0400  
www.smc Pneumatics.ca

